高温下页岩水化损伤的各向异性实验研究

卢运虎^{1,2*}, 梁川³, 金衍^{1,2}, 陈勉^{1,2}

1. 油气资源与工程国家重点实验室, 北京 102249;

2. 中国石油大学(北京)石油工程学院, 北京 102249;

3. 中国石油海洋工程有限公司, 北京 100028

*联系人, E-mail: luyunhu20021768@163.com

收稿日期: 2017-08-14; 接受日期: 2017-09-13; 网络出版日期: 2017-10-11

国家自然科学基金(编号: 51774305, 51490650)资助项目

摘要 为了研究高温页岩水化损伤的各向异性特征, 以龙马溪页岩为例, 利用FEI Qemscan 650F型矿物定量分析-热场发射环境扫描电子显微镜(EDS-FESEM), 系统观察不同温度、压力和浸泡时间下页岩平行层理和垂直层理面特征黏土矿物及微观结构变化特征. 研究表明, 龙马溪页岩细观尺度的各向异性引起页岩水化特征存在明显区别, 即平行层理面表现为大量微纳米溶蚀孔伴生发育的原生裂隙膨胀、闭合、塌陷的损伤模式, 而垂直层理面表现为大量微纳米长石矿物溶蚀孔隙的损伤模式. 相同浸泡时间和压力下, 温度越高页岩细观结构的水化损伤越快; 相同温度和压力下, 随着浸泡时间增加, 页岩细观结构的水化程度先增大后逐渐趋于平缓, 温度升高减小了页岩水化特征时间, 其内在联系需进一步开展实验探讨.

关键词 页岩, 各向异性, 水化损伤, 微观特征, 高温

PACS: 47.27.-i, 47.27.Eq, 47.27.Nz, 47.40.Ki, 47.85.Gj

水平井钻井和水力压裂是实现页岩气高效开发的关键技术^[1]. 受沉积和构造运动影响, 页岩非均质性强, 各向异性特征显著, 高温、高应力与入井流体化学耦合作用下页岩物理力学特性演化规律不明确, 给钻井与压裂设计带来巨大的挑战, 如何有效确定流体作用下页岩各向异性特征显得尤为重要^[2-9].

与传统岩石不同, 页岩黏土矿物的定向排列和温度、压力条件下有机质成熟度引起孔隙结构的差异构成了页岩独特的组构特征, 页岩各向异性及其分布规律必将影响页岩的水化进程. 国内外学者借助高

性能微观扫描设备在页岩微观组构及水化特性试验方面开展了大量的工作, Powers^[10]借助CT定位页岩中孔隙裂缝连通发育区, 再用扫描电子显微镜(Scanning Electron Microscope, SEM)剖析其孔隙结构、矿物颗粒和断裂填充等特征. Goral等人^[11]将微纳米X射线显微镜(XRM)与SEM相结合, 提出页岩纳米尺度结构异质性的表征方法. 石秉忠和夏柏如^[12]利用XRD, SEM和CT观察了硬脆性页岩水化阶段微观结构变化, 发现吸水弱化矿物接触界面引起微裂纹拓展演变. 刘敬平和孙金声^[13]利用SEM观察了水化后龙马溪组页岩的

引用格式: 卢运虎, 梁川, 金衍, 等. 高温下页岩水化损伤的各向异性实验研究. 中国科学: 物理学 力学 天文学, 2017, 47: 114614
Lu Y H, Liang C, Jin Y, et al. Experimental study on hydration damage of anisotropic shale under high temperature (in Chinese). Sci Sin-Phys Mech Astron, 2017, 47: 114614, doi: 10.1360/SSPMA2017-00217

微观组构,发现浸水后微孔洞明显增多微裂缝出现延展. 马天寿和陈平^[14]通过CT扫描观察了不同水化程度页岩微观损伤特征,发现页岩损伤主要发生在水化初期. Liu等人^[15]通过SEM观察到水侵页岩微裂纹的全过程,随着水浸时间增加,微裂纹会相互传播、分岔和连接,最终会发展成宏观裂缝. Massat等人^[16]利用SEM和CT观察了蒙脱石水化对页岩微结构和孔隙分布的影响,发现膨胀压力达到峰值致使微裂纹破坏扩展. 刘向君等人^[17]开展了硬脆性页岩水化过程微观组构表征研究,发现硬脆性页岩定向排列的矿物颗粒为水化吸水提供通道,且形成微裂纹主要平行层理裂缝. 前期学者的研究讨论了页岩的微观孔隙、层理发育特征,从微观角度出发阐述了页岩水化过程微裂纹的行为特点,为页岩的水化行为研究奠定了基础. 然而,却很少有学者研究不同层理方向的页岩水化特征^[17-22].

为了研究高温高压页岩水化损伤的各向异性特征,以龙马溪页岩为例,利用FEI Qemscan 650F型矿物定量分析-热场发射环境扫描电子显微镜(Energy Dispersive Spectroscopy-Field Emission Scanning Electron Microscope, EDS-FESEM)对不同温度、压力和水化时间下层理面和垂直层理面特征黏土矿物及微观结构变化特征,以揭示龙马溪组页岩水化的各向异性特性及制定页岩储层井壁稳定及水力压裂相关入井流体设计提供实验基础.

1 页岩微观组构及理化特征

1.1 页岩样品的地球化学参数和矿物组分

样品取自四川省宜宾市珙县YS-B井下志留系龙马溪组页岩,试件地球化学参数和矿物组分见表1.

1.2 微观结构

从图1电子显微镜扫描照片来看,龙马溪页岩平行

层理方向可见矿物平铺式定向排列;垂直层理面方向可见大量微米级裂缝,缝宽在0.1–40 μm 之间.

1.3 样品的制备

为防止制样对页岩样品造成人为缺陷,首先,采用液氮沿层理面和垂直层理面钻取岩芯片;其次,采用环氧树脂对所有样品进行注胶固定保护,机械抛光仪减薄样品;最后,采用氩离子抛光仪对样品表面进行处理,消除制样引起的不平整表面(图2).

2 实验设备及方案

2.1 实验设备

实验设备为FEI Qemscan 650F型矿物定量分析-热场发射环境扫描电子显微镜,可同时容纳14个直径小于30 mm的试样,其分辨率最高为1.2 nm. 在高真空环境下采用背散射电子探头模式(BSED)和二次电子探头模式(ETD)分别对页岩层理面和垂直层理的细观结构和形貌进行表征(图3).

水化过程模拟主要采用GGS42型高温高压失水仪和高压氮气来提供温度和压力环境,工作最高温度为150°C,工作极限压力为6 MPa(图4).

2.2 实验方案及步骤

(1) 采用EDS-FESEM对全部原始样品的细观结构进行表征,标记观察的微区位置.

(2) 按照表2实验方案,将样品分别置于不同的高温高压的流体环境进行浸泡.

(3) 取出浸泡样品后,将样品抽真空冷冻干燥,并对样品喷碳.

(4) 采用EDS-FESEM对已标记位置的Fe, Mg蒙脱石与伊利石构成的裂隙表面结构进行表征.

3 结果与分析

3.1 页岩平行层理面水化特征

由于页岩制样困难,实验过程中主要通过能谱仪和高分辨率场发射电子显微镜监测蒙脱石与伊利石接触面. 在80°C和120°C浸泡条件下,平行层理取心页岩水化过程显示出相似的变形和破坏过程:由伊利石(云母)和蒙脱石构成的纳米级裂隙壁面经历了前期膨

表1 页岩地球化学参数和矿物组分

Table 1 Geochemical parameters and mineral compositions of shale samples

采样深度 (m)	TOC (%)	干酪根类型	矿物组分 (%)					
			石英	长石	方解石	白云石	黄铁矿	黏土
2321	1.78	III	31.0	11.4	12.9	5.1	1.2	38.4
2324	2.85	III	31.7	5.5	8.3	5.9	3.6	45.0

图1 (网络版彩图)龙马溪组页岩电子显微镜扫描照片. (a) 平行层理方向; (b) 垂直层理面方向

Figure 1 (Color online) Microcosmic structures and compositions of Longmaxi shale under scanning electron microscope (SEM). (a) The observations paralleled to shale beddings; (b) the observations vertical to shale beddings.

图2 (网络版彩图)预处理后页岩样品

Figure 2 (Color online) Shale sample of preliminary preparation.

图3 (网络版彩图)矿物定量分析-热场发射环境扫描电子显微镜

Figure 3 (Color online) FEI Qemscan 650F energy dispersive spectroscopy (EDS)-field emission scanning electron microscope (FESEM).

胀变窄, 中期膨胀闭合, 后期的裂隙塌陷, 形成与层理面近似平行的次生裂隙的裂缝扩展模式. 同时, 样品上新发育出大量微纳米尺度长石溶蚀孔(图5和6).

随着温度的升高, 在相同浸泡天数下, 平行层理取心页岩样品的水化程度明显增大, 即120°C条件下浸

图4 (网络版彩图)高温高压失水仪
Figure 4 (Color online) GGS42 HTHP filter press.

表2 不同浸泡时间、温度条件下的样品信息^{a)}

Table 2 Shale samples under different soaking time and temperature conditions

浸泡时间(d)	温度 (°C)(压力: 3.5 MPa)	
	120	80
1	YS-01, YS-02	YS-07, YS-08
2	YS-11, YS-12	YS-15, YS-16
3	YS-03, YS-04	YS-09, YS-10
4	YS-13, YS-14	YS-17, YS-18
5	YS-05, YS-06	YS-19, YS-20

a) 编号奇数为平行层理面, 偶数为垂直层理面

图5 (网络版彩图)不同浸泡时间页岩平行层理水化特征(80°C). (a) 浸泡1 d前、后; (b) 浸泡2 d前、后; (c) 浸泡3 d前、后; (d) 浸泡4 d前、后; (e) 浸泡5 d前、后

Figure 5 (Color online) Observations of shale hydration characteristics under different soaking time from beddings-parallel direction (80°C). (a) Shale characteristics around 1 d soaking; (b) shale characteristics around 2 d soaking; (c) shale characteristics around 3 d soaking; (d) shale characteristics around 4 d soaking; (e) shale characteristics around 5 d soaking.

泡的样品在第1天表现出明显的水化膨胀性, 纳米级裂隙几乎闭合. 第4天已发生塌陷形成明显的裂隙面, 随着浸泡时间增加, 损伤特征不明显. 但是, 80°C条件下样品在第3天才表现出明显的膨胀闭合性, 到第5天有塌陷的迹象(图6).

3.2 页岩垂直层理面水化特征

无论是80°C还是120°C温度的浸泡环境, 在5 d的

水化测试时间内并未观察到垂直层理取心页岩样品上生成新裂缝, 而是新发育了大量微纳米长石矿物溶蚀孔隙. 随着浸泡温度和浸泡时间的增加, 垂直层理取心页岩样品上新生成的溶蚀孔隙的大小、体积和分布密度在增大(图7和8).

通过对整个浸泡周期的观察, 样品的黏土矿物和长石矿物含量及其分布、样品有机质含量均会影响微纳米尺度溶蚀孔隙的发育(图8).

图 6 (网络版彩图)不同浸泡时间页岩平行层理水化特征(120°C). (a) 浸泡1 d前、后; (b) 浸泡2 d前、后; (c) 浸泡3 d前、后; (d) 浸泡4 d前、后; (e) 浸泡5 d前、后

Figure 6 (Color online) Observations of shale hydration characteristics under different soaking time from beddings-parallel direction (120°C). (a) Shale characteristics around 1 d soaking; (b) shale characteristics around 2 d soaking; (c) shale characteristics around 3 d soaking; (d) shale characteristics around 4 d soaking; (e) shale characteristics around 5 d soaking.

图 7 (网络版彩图)不同浸泡时间页岩垂直层理面水化特征(80°C). (a) 浸泡1 d前、后; (b) 浸泡2 d前、后; (c) 浸泡3 d前、后; (d) 浸泡4 d前、后; (e) 浸泡5 d前、后

Figure 7 (Color online) Observations of shale hydration characteristics under different soaking time from beddings-vertical direction (80°C). (a) Shale characteristics around 1 d soaking; (b) shale characteristics around 2 d soaking; (c) shale characteristics around 3 d soaking; (d) shale characteristics around 4 d soaking; (e) shale characteristics around 5 d soaking.

图8 (网络版彩图)不同浸泡时间页岩垂直层理面水化特征(120°C). (a) 浸泡1 d前、后; (b) 浸泡2 d前、后; (c) 浸泡3 d前、后; (d) 浸泡4 d前、后; (e) 浸泡5 d前、后

Figure 8 (Color online) Observations of shale hydration characteristics under different soaking time from beddings-vertical direction (120°C). (a) Shale characteristics around 1 d soaking; (b) shale characteristics around 2 d soaking; (c) shale characteristics around 3 d soaking; (d) shale characteristics around 4 d soaking; (e) shale characteristics around 5 d soaking.

通过页岩原位浸泡实验,发现高温条件下页岩平行和垂直层理微区水化损伤特征各异,平行层理面表现为大量微纳米溶蚀孔伴生发育的原生裂隙膨胀、闭合、塌陷的裂缝的损伤模式,而垂直层理面表现大量微纳米长石矿物溶蚀孔隙的水化特征.

在相同的温压条件下,浸泡时间增加,页岩平行层理和垂直层理的水化程度先增大后逐渐趋于平缓.受页岩沉积各向异性的影响,在平行层理方向,80°C条件下,浸泡3 d原生裂隙才发生膨胀闭合、5 d塌陷形成水化裂缝,水化进程减缓;在120°C条件下,1 d原生裂隙发生膨胀闭合、4 d塌陷形成裂缝,水化进程减缓.在垂直层理方向,随着浸泡时间增加,微纳米长石矿物溶蚀孔隙体积、密度增大并呈现减缓趋势.水化浸泡的特征时间对温度敏感性强,对于水化特征与温度、特征时间需要进一步开展详细的实验工作进行讨论.

4 结论

(1) 发现龙马溪页岩细观尺度存在明显各向异性,在层理表面以纳米孔隙较为发育,有机质孔、骨架矿物孔、黏土粒间孔等密集分布;在层理断面上成岩缝较发育,有机质或沥青质胶结.

(2) 各向异性特性引起页岩水化特征存在明显区别,即平行层理面上为大量微纳米溶蚀孔伴生发育的原生裂隙膨胀、闭合、塌陷的损伤模式,而垂直层理面为大量微纳米长石矿物溶蚀孔隙的损伤模式.

(3) 相同浸泡时间和压力下,温度越高页岩细观结构的水化损伤越快;相同温度和压力下,随着浸泡时间增加,页岩细观结构的水化程度先增大后逐渐趋于平缓,温度的升高减小了页岩水化特征时间,其内在联系需进一步开展实验探讨.

参考文献

- 1 Chen M, Ge H K, Zhao J Z, et al. The key fundamentals for the efficient exploitation of shale oil and gas and its related challenges (in Chinese). *Petrol Drill Tech*, 2015, 43: 7–14 [陈勉, 葛洪魁, 赵金洲, 等. 页岩油气高效开发的关键基础理论与挑战. *石油钻探技术*, 2015, 43: 7–14]

- 2 Niandou H, Shao J F, Henry J P, et al. Laboratory investigation of the mechanical behaviour of Tournemire shale. *Int J Rock Mech Min Sci*, 1997, 34: 3–16
- 3 Sone H, Zoback M D. Mechanical properties of shale-gas reservoir rocks—Part 1: Static and dynamic elastic properties and anisotropy. *Geophysics*, 2013, 78: D381–D392
- 4 Dewhurst D N, Siggins A F. Impact of fabric, microcracks and stress field on shale anisotropy. *Geophys J Int*, 2006, 165: 135–148
- 5 Makhhanov K, Habibi A, Dehghanpour H, et al. Liquid uptake of gas shales: A workflow to estimate water loss during shut-in periods after fracturing operations. *J Unconvent Oil Gas Resour*, 2014, 7: 22–32
- 6 Yuan W, Li X, Pan Z, et al. Experimental investigation of interactions between water and a lower silurian Chinese shale. *Energ Fuels*, 2014, 28: 4925–4933
- 7 Rybacki E, Reinicke A, Meier T, et al. What controls the mechanical properties of shale rocks?—Part I: Strength and Young's modulus. *J Pet Sci Eng*, 2015, 135: 702–722
- 8 Waters G A, Lewis R E, Bentley D. The effect of mechanical properties anisotropy in the generation of hydraulic fractures in organic shales. In: Proceedings of SPE Annual Technical Conference and Exhibition. Society of Petroleum Engineers, 2011
- 9 Gehne S, Benson P, Koor N, et al. Fluid driven fracture mechanics in highly anisotropic shale: A laboratory study with application to hydraulic fracturing. In: 19th EGU General Assembly, EGU2017. Vienna, 2017. 1597
- 10 Powers M R. Exploring Micro X-ray Computed Tomography Coupled with Scanning Electron Microscopy as Tools for Paleozoic Shale Studies. Dissertation for the Masteral Degree. Oklahoma: Oklahoma State University, 2015
- 11 Goral J, Miskovic I, Gelb J, et al. Correlative XRM and FIB-SEM for (non) organic pore network modeling in woodford shale rock matrix. In: Proceedings of International Petroleum Technology Conference. Doha, Qatar: International Petroleum Technology Conference, 2015
- 12 Shi B Z, Xia B R. The variation of microstructures in the hard brittle shale hydration process (in Chinese). *J Daqing Petrol Inst*, 2011, 35: 28–34, 124 [石秉忠, 夏柏如. 硬脆性泥页岩水化过程的微观结构变化. 大庆石油学院学报, 2011, 35: 28–34, 124]
- 13 Liu J P, Sun J S. Borehole wall collapse and control in shale gas well drilling (in Chinese). *Drill Fluid Complet Fluid*, 2016, 33: 25–29 [刘敬平, 孙金声. 页岩气藏地层井壁水化失稳机理与抑制方法. 钻井液与完井液, 2016, 33: 25–29]
- 14 Ma T S, Chen P. Study of meso-damage characteristics of shale hydration based on CT scanning technology (in Chinese). *Petrol Explor Dev*, 2014, 41: 227–233 [马天寿, 陈平. 基于CT扫描技术研究页岩水化细观损伤特性. 石油勘探与开发, 2014, 41: 227–233]
- 15 Liu X, Zeng W, Liang L, et al. Experimental study on hydration damage mechanism of shale from the Longmaxi Formation in southern Sichuan Basin, China. *Petroleum*, 2016, 2: 54–60
- 16 Massat L, Cuisinier O, Bihannic I, et al. Swelling pressure development and inter-aggregate porosity evolution upon hydration of a compacted swelling clay. *Appl Clay Sci*, 2016, 124–125: 197–210
- 17 Liu X J, Xiong J, Liang L X. Hydration experiment of hard brittle shale of the longmaxi formation (in Chinese). *J Southwest Petrol Univ (Sci Tech Ed)*, 2016, 38: 178–186 [刘向君, 熊健, 梁利喜. 龙马溪组硬脆性页岩水化实验研究. 西南石油大学学报(自然科学版), 2016, 38: 178–186]
- 18 Dehghanpour H, Lan Q, Saeed Y, et al. Spontaneous imbibition of brine and oil in gas shales: Effect of water adsorption and resulting microfractures. *Energ Fuels*, 2013, 27: 3039–3049
- 19 Dehghanpour H, Zubair H A, Chhabra A, et al. Liquid intake of organic shales. *Energ Fuels*, 2012, 26: 5750–5758
- 20 Ma T, Chen P. Study of meso-damage characteristics of shale hydration based on CT scanning technology. *Pet Explor Dev*, 2014, 41: 249–256
- 21 Zhang S, Sheng J J. Study of the propagation of hydration-induced fractures in mancos shale using computerized tomography. *Int J Rock Mech Min Sci*, 2017, 95: 1–7
- 22 Lee S, Fischer T B, Stokes M R, et al. Dehydration effect on the pore size, porosity, and fractal parameters of shale rocks: Ultrasmall-angle X-ray scattering study. *Energ Fuels*, 2014, 28: 6772–6779

Experimental study on hydration damage of anisotropic shale under high temperature

LU YunHu^{1,2*}, LIANG Chuan³, JIN Yan^{1,2} & CHEN Mian^{1,2}

¹ State Key Laboratory of Petroleum Resource and Prospecting, Beijing 102249, China;

² Petroleum Engineering, China University of Petroleum (Beijing), Beijing 102249, China;

³ CNPC Offshore Engineering Company Ltd, Beijing 100028, China

The Longmaxi shale samples are used to investigate the anisotropic hydration damage characteristics of shale under high temperature conditions. The FEI Qemscan 650F energy dispersive spectroscopy (EDS)-field emission scanning electron microscope (FESEM) is used to help observe the evolution characteristics of shale clay mineral and micro-structure under different temperature, pressure and soaking time conditions from beddings vertical and parallel directions. It comes to the conclusion that the hydration characteristic induced by microscale anisotropy of Longmaxi shale varies a lot. The damage behavior in the bedding-parallel plane is characterized by dilatation-closure-collapse process of primary fractures which exists in a large amount of nano-scale and micro-scale corrosion pores. While the damage behavior in the bedding-vertical plane is mainly represented as a mass of nano-scale and micro-scale corrosion pores. It's also found that the shale hydration damage is faster under higher temperature condition when the soaking time and pressure are the same. Besides, under the same temperature and pressure conditions, the shale microstructure hydration process trends to increase at the beginning and be flat at last. The higher temperature shorten the time spending on shale hydration and its inner relationship is required more experiments.

shale, anisotropy, hydration damage, microcharacteristic, high-temperature

PACS: 47.27.-i, 47.27.Eq, 47.27.Nz, 47.40.Ki, 47.85.Gj

doi: [10.1360/SSPMA2017-00217](https://doi.org/10.1360/SSPMA2017-00217)