数字体图像相关方法研究进展

潘兵*, 王博

北京航空航天大学固体力学研究所, 北京 100191

* 联系人, E-mail: panb@buaa.edu.cn

2016-07-15 收稿, 2016-09-28 修回, 2016-09-29 接受, 2017-01-21 网络版发表

国家自然科学基金(11002012, 11272032, 11427802)、国家自然科学基金优秀青年科学基金(11322220)、北京市科技新星计划(xx2014B034)和中央高校基本科研业务费专项资助

摘要 数字体图像相关方法是可测量物体内部三维全场变形的先进实验力学方法. 通过匹配由数字体成像设备获取的被测物体变形前后的两组数字体图像, 该方法能够获得物体内部亚体素精度的三维位移场和全场应变. 得益于新型体成像设备的不断涌现、图像配准算法的持续改进以及高性能并行计算技术的快速发展, 数字体图像相关方法已在生物医学、固体力学、岩土力学、材料科学等领域获得许多令人瞩目的重要应用. 本文对过去20多年数字体图像相关方法中出现的各种位移和应变测量算法进行了系统回顾和评述, 分析了该方法当前的局限和所面临的挑战. 可以预期, 数字体图像方法在实验力学领域中将扮演更为重要的角色, 并有望在更多科研和工程领域中获得应用.

关键词 数字体图像相关, 内部变形测量, 实验力学

位移和应变场的准确测量一直是实验力学最基本的任务. 近1个世纪以来, 受益于不同物理分支学科(如电磁学、光学等)的快速发展, 各种新的位移和应变测量技术层出不穷. 目前, 工程中广泛采用的位移/应变测量手段主要包括: 以位移计、应变电测、光栅光纤为代表的接触式测量技术; 以基于相干光干涉原理(全息干涉、电子散斑干涉、云纹干涉等)或图像识别原理(网格法、数字图像相关方法等)为代表的非接触式应变测量技术. 然而, 已有的各种位移和应变测试手段, 除了少数埋入式的位移应变传感器外, 绝大多数只能用于材料或结构表面变形测量. 在载荷、几何结构以及材料内部组成稍微复杂的情况下(如非面内加载、复杂几何外形或内部结构、非均质材料等), 仅仅依靠表面变形信息往往不能满足力学分析和材料研究的要求.

因而, 准确地获取各种固体材料或结构(如复合材料、生物组织、合金材料等)在不同载荷状态下的

内部三维全场变形, 建立载荷-内部变形之间的关系, 将有助于更全面、准确地分析材料或结构在各种复杂外载荷作用下的力学行为和表征其基本力学参数, 亦可为验证广泛使用的三维有限元方法提供更为真实有力的实验技术手段. 由此可见, 发展一种实用、准确的内部三维变形场测量技术, 其科学价值和应用前景毋庸置疑.

在各种非接触全场光测力学方法中, 数字图像相关方法(digital image correlation, DIC)^[1,2]因具有实验设备及测量过程简单、抗干扰能力强、适用测量范围广泛等突出优点被认为是当前实验固体力学最重要、最受欢迎和应用最广泛的变形测量技术. 然而已有的2D-DIC, 3D-DIC仅可用于表面变形测量, 1999年为了获得松质骨试样在压缩载荷作用下的内部变形场, Bay等人^[3]将DIC方法推广至三维, 提出数字体图像相关方法(digital volume correlation, DVC), 通过匹配由显微CT记录的松质骨在变形前后状态下的两组

引用格式: 潘兵, 王博. 数字体图像相关方法研究进展. 科学通报, 2017, 62: 1671-1681

Pan B, Wang B. Research progress in digital volume correlation method (in Chinese). Chin Sci Bull, 2017, 62: 1671-1681, doi: 10.1360/972016-00606

体图像,获得松质骨在特定的压缩载荷作用下内部三维全场位移和全场应变.在该创新思想的启发下,研究人员先后将DVC与各种体成像设备(X射线计算机断层扫描^[4,5]、核磁共振成像^[6]、激光扫描共焦显微镜^[7]、光学相干断层成像术^[8]等)结合,不断拓展DVC方法应用范围.借助于这些功能各异的体成像设备,DVC的应用对象也在不断丰富:从最初的生物力学中骨骼力学行为的研究^[9~13],逐渐拓展到细胞^[14~17]、软组织^[18~21]和植入物^[22,23]等,并被用于实验力学中三维裂纹的局部变形研究^[24~29]和非均匀材料内部参数识别^[30,31],以及各种天然材料(木材^[32,33]、沙土^[34~36]、岩石^[37~39]等)和人工合成材料(复合材料^[40~44]、蜂窝泡沫^[45~48]等)的力学研究.

作为一种可测量物体内部三维全场变形的先进实验力学测试技术,DVC方法的重要性和应用前景不言而喻.为使该方法的研究人员和使用者能更快速和全面地了解DVC的技术现状,本综述首先介绍了DVC的基本原理,随后对其中的位移/应变测量算法进行了详细和系统的评述,并总结了该方法当前的局限性和所面临的挑战.

1 数字体图像相关方法研究进展

1.1 DVC方法的基本原理

与用于表面变形测量的DIC方法类似,DVC方法测量物体内部变形的过程亦分为如下3步(图1): (1) 数字体图像采集.采用体成像设备对不同加载阶段的试样进行扫描,重建被测试样的三维数字体图像; (2) 三维位移场测量.利用局部或全局DVC算法确定在参考体图像中选定的各离散计算点在变形前后体图像中的位置坐标,从而获得计算区域的三维位移矢量场; (3) 三维应变场计算.采用合适的数值算法(如差分算法、拟合方法等)从三维位移场中提取三维应变场.由于三维应变场是通过三维位移场处理后处理获得的,因此如何提高三维位移场的测量精度是DVC方法研究的关键.

在DIC测量时操作者可在被测试样表面制作人工散斑图案以提供高对比度的变形信息载体^[49].然而在绝大多数情况下,DVC方法只能依赖被测物体内部的复杂成分或微结构体系在体图像中形成的灰度差异作为变形信息载体(当然在某些特殊情况下可用混入其中的微颗粒作为标记来进行图像位移跟

踪^[50,51]).为确定某一计算点的三维位移矢量,需围绕该点选择包含足够灰度对比度的立方体参考图像子体块(reference sub-volume),并建立一个可定量评价参考图像子体块和待寻找的目标图像子体块(target sub-volume)相似程度的目标函数(correlation criterion)^[52,53].由于目标图像子体块可能出现包括平移、转动、均匀应变甚至更为复杂的非均匀变形,因而需要采用形函数(通常为包括12个变量的一阶形函数)来近似其内部变形,再通过数值优化算法和灰度插值算法相结合来优化目标函数,以在变形后体图像中寻找与图像子体块最为相似的目标图像子体块,从而确定其当前体素点(参考图像子体块中心点)的位移矢量.此外,在建立目标函数的时候,需考虑实际实验过程中由于各种不稳定因素造成的图像灰度变化引入的误差. Pan等人^[53]之前的研究建议选择对目标图像子体块灰度线性变化不敏感的零均值归一化互相关函数(或与之等价的零均值归一化最小平方距离相关函数),因其能提供更好的抗噪声能力.灰度插值算法的选择也很丰富^[54,55],但需根据实际情况综合考虑插值精度和计算量,一般推荐使用3次B样条插值^[55].

1.2 位移测量算法

为实现全场三维位移测量,DVC方法需先后执行两个步骤:整体素位移搜索(或初值估计)和亚体素位移测量^[56~58].通过简单的整体素搜索,DVC能快速确定各计算点的整体素位移.随后,为了进一步提高测量精度,可采用亚体素配准算法获得亚体素位移,这一过程通常被认为是DVC提供测量精度的关键.

1.2.1 整体素匹配算法

一般情况下,参考与变形体图像之间的相对变形与转动较小,因此可通过简单的空域或频域搜索算法来获取整体素精度的位移初始估计.空域整体素位移搜索算法通常基于相关函数在变形体图像的指定范围内逐点地搜索相似度最大的整体素位置来计算该点的整体素位移^[3].为了提高计算效率,空域搜索策略可采用粗精搜索法^[59]、扩展搜索法^[60]、基于递归策略的全局求和表方法^[61]等改进策略.当然,整体素位移搜索也可在频域中执行,借助于三维快速傅里叶变换^[62,63](fast Fourier transform, FFT)可实现高效的频域相关匹配.尽管整体素相关匹配的搜索策略在大多数情况下(如刚体平移、小转动、小应

图1 (网络版彩色)数字体图像相关方法的测量过程。(a) CT扫描; (b) 体图像重建; (c) 三维位移场测量

Figure 1 (Color online) Implementation procedure of DVC. (a) CT scanning; (b) volume image reconstruction; (c) 3D displacement measurement

变等)可获得较为准确的位移初值, 这些方法并不适合于变形体图像存在大变形或大转动的情况。

需要说明的是, 为避免各计算点整体素位移的重复搜索和实质性地提高DVC方法的适用性和计算效率, Pan等人^[64,65]将可靠性导向位移跟踪(reliability-guided displacement tracking, RGDT)策略用于DVC的初值估计, 该方法通过位移传递函数将已计算点的位移分量和位移梯度分量自动传递给当前计算点作为变形初值估计, 从而仅需要在种子点处执行整体素位移搜索。该策略不仅能够有效避免整体素搜索的繁琐和重复运算, 而且能够适应大变形或大转动等特殊情况。

1.2.2 亚体素配准算法

按照配准算法的不同, DVC中的亚体素位移测量算法^[66-68]可分为: 基于子体块的局部DVC方法和基于网格单元的全局DVC方法。这两种DVC方法通常都采用整体素匹配运算获取整体素位移作为初值估计, 随后通过特定的数值算法(非线性优化算法、梯度法或峰值查找算法等)将位移精确至亚体素精度。

如图2所示, 局部DVC方法通常基于运动场(包括位移场和应变场)的局部描述来跟踪以每个计算点为中心的参考子体块在变形体图像中的相应位置。局部DVC方法独立跟踪各计算点, 且各子体块间没有预先施加连续性条件, 因此变形子体块间可能会

分离或重叠。与之不同的是, 全局DVC方法基于整个位移场的全局描述, 通常采用有限单元理论来划分计算区域。全局DVC方法同时跟踪变形体图像中的所有单元, 因而能够同时确定所有单元节点的位移。由于相互关联的单元共用相同节点, 因此相邻单元之间满足位移连续性。

(i) 基于子体块的局部DVC方法。基于子体块的局部DVC方法通常也分为空域和频域两种算法。为了获取亚体素精度的位移, 空域算法通常采用非线性迭代算法, 用于优化求解这种不适定问题。这种算法通常是利用迭代运算的方式使非线性问题由变形矢量的初始值逐渐收敛至局部最佳极值(即, 使得参考和变形子体块的匹配程度最佳的变形矢量)。在DVC方法发展初期, 研究工作大多都集中关注如何完善位移形函数以准确描述目标子体块的变形。最初Bay等人^[3]仅考虑了3个刚体位移分量, 采用Levenberg-Marquardt (LM)算法来进行亚体素位移测量。为了更准确地表征目标子体块的变形, Smith等人^[59]考虑了体图像可能存在刚体转动, 在形函数中引入了额外的3个转动分量, 并采用Broyden-Fletcher-Goldfarb-Shanno (BFGS)拟牛顿算法提高计算效率。Verhulp等人^[69]将位移形函数扩展至12个自由度(又称线性位移或一阶形函数), 并采用BFGS拟牛顿算法获得更优的位移结果。在此之后, 一阶形函数开始获得广泛应用。

图2 (网络版彩色)局部和全局DVC方法示意图。(a) 基于子体块的局部DVC; (b) 基于体单元的全局DVC

Figure 2 (Color online) Schematic of local and global DVC. (a) Sub-volume-based local DVC; (b) element-based global DVC

研究人员开始转而关注非线性优化算法的选择问题,继LM算法和BFGS算法之后,ZaueI等人^[70]、Germaneau等人^[50,51]、牛永强等人^[71]以及潘兵等人^[72]采用算法原理简单的最速下降算法(又称梯度法)进行亚体素配准运算;Huang等人^[61]采用真实实验比较了梯度法和牛顿-拉夫森(Newton-Raphson, NR)算法,验证了NR方法具有更高的位移精准度。随后,Jandejsek等人^[73]将与高斯牛顿(Gauss-Newton, GN)算法等价的Lucas-Kanade算法^[74]应用到DVC方法中;Pan等人^[64,75]将最小二乘迭代策略应用到梯度法中,建立了一种与NR算法等价但原理和实现更为简单的三维迭代最小二乘(3D ILS)算法。最近,Pan等人^[65]发展了一种三维反向组合-高斯牛顿(inverse compositional Gauss-Newton, IC-GN)算法,获得了比传统NR方法更优的位移结果和抗噪声干扰能力。

除了上述的各种非线性优化方法,亚体素配准方法也采用局部相关系数峰值拟合法或峰值查找(peaking-finding)算法来确定各计算点在变形后的亚体素位置。该算法首先确定已通过空域或频域搜索到的目标整体素点周围一定范围内(如 $3 \times 3 \times 3$ 体素)的离散相关系数矩阵,随后采用不同的拟合或插值函数确定相关系数最大处的亚体素位置。Roeder等人^[62]采用高斯函数近似拟合相关系数矩阵。汪敏等人^[76]和Franck等人^[7]采用三元二次多项式拟合峰值附近的相关函数,后者还结合一种拉伸相关(stretch-corre-

lation)算法以适应大变形测量。Mao等人^[39,77]则采用3次样条插值对局部相关系数进行插值。最近,Bar-Kochba等人^[78]将一种迭代优化的策略应用到频域配准方法中,建立了一种快速迭代的DVC (fast iterative DVC, FIDVC)方法,显著提升了该方法在非线性三维变形测量方面的精准度。然而局部相关系数峰值查找法没有考虑目标子体块的局部变形,其精度要劣于空域迭代互相关方法。

(ii) 基于体单元的全局DVC方法。如前所述,全局DVC方法通常采用有限元理论来描述体图像的三维变形。在将FEM结合至DVC技术之初,Roux等人^[79]发展了一种基于8节点立方体单元的DVC方法(C8-DVC),该方法采用8节点立方体单元和分段三次线性函数(C8P1单元)描述全场位移。作为改进,Rthor等人^[80]通过结合扩展有限元的思想建立了扩展的C8-DVC (extended C8-DVC, X-C8-DVC)方法,该方法通过引入强化的位移形函数弥补了原有算法在非连续变形(如裂纹)情况下的缺陷,提升了全局DVC方法的计算精准度和实用性。

然而,全局DVC方法自身的固有缺陷在于:空间分辨率与位移不确定度之间的矛盾。较高的位移数据密度(空间分辨率)需要细化网格,从而导致较大的位移波动(位移不确定度,随机误差);较高的位移精度势必会以损失空间分辨率为代价。因此为提升高空间分辨率情况下的位移精度,Leclerc等人^[81]发展了一种结合灰度相关函数、平衡间隙法和边界正则化方法的基于体素的全局DVC方法(voxel-based DVC, V-DVC)。类似地,Fedele等人^[82]将Galerkin有限元思想应用到全局DVC方法中,并采用结合了图像金字塔和吉洪诺夫(Tychonoff)正则化的多重网格法作为算法特性,同样获得数据稳健的三维变形结果。Gomes等人^[83]发展了一种基于广义本征分解(proper generalized decomposition, PGD)的DVC方法,该方法采用多重网格PGD以及吉洪诺夫正则化(Tikhonov regularization)提高算法的鲁棒性。以上3种方法通过优化力学正则化的目标函数来削减小单元尺寸情况下的显著测量误差,使得DVC方法能够在不同尺度下(尤其是小单元尺寸情况下)获得精准、稳定的三维位移结果。

由于算法实现的复杂性,全局DVC方法的计算效率通常远低于局部DVC方法,因此如何改进算法以提升全局DVC的运算速度也是研究人员关注的问

题之一。Mortazavi 等人^[84]将三维改进的频谱法(improved spectral approach, ISA)应用到全局DVC方法中,建立了一种IS-DVC方法,该方法通过使用位移场基底的傅里叶分解以及FFT方法将复杂的频域位移等式转化成简单的空域等式,从而避免了因自由度增加(即网格密集化)导致的计算量剧增的难题。

在DIC方法中,关于基于图像子区的局部DIC方法和基于有限单元的全局DIC方法性能比较已经有明确的结论^[85,86]:在图像子区尺寸较大的情况下,局部算法的位移测量精准度要优于全局算法。然而,在比较DVC方法中的局部和全局算法时,Tozzi等人^[66]以及Madi等人^[68]得出相反的结论:全局DVC算法的位移和应变精准度优于局部DVC算法。需要指出的是,文献[66~68]使用的局部DVC算法并不是基于子体块的非线性迭代优化算法,而是基于相关系数曲面拟合的峰值查找算法。因此公正地比较DVC中的局部和全局算法性能仍需进一步的深入研究。

1.3 应变测量算法

力学研究往往更关注材料和结构的全场应变分布,准确的应变场更是一系列深入研究(如裂纹萌生和扩展机制、力学参数的反演识别等)的基础。通过位移测量算法,DVC能够得出被测物体在当前载荷状态下的三维全场位移,甚至位移梯度。根据位移梯度与应变的等价关系,应变结果能够通过已确定的位移梯度分量直接获得。然而,在进行三维位移测量过程中,由于受噪声、伪影等外因以及算法自身因素的影响,测量的位移梯度往往(尤其在小应变情况下)并不可靠。因此在应变求解过程中,研究人员通常关注的是如何由包含噪声的位移分量获取相应的应变分量。归纳起来,现有的三维应变测量方法主要包含:平滑位移场差分法、局部多项式拟合法以及有限元框架微分法。

(i) 平滑位移场差分法。基于位移和应变的微分关系,最为直接的应变计算方法是对位移结果进行差分运算来提取应变分量。然而,数值差分会放大包含在位移场中的噪声,从而会降低应变分量的测量精度。因此在差分运算之前,对含噪声的位移数据进行平滑处理十分必要。由于平滑后的位移场中噪声水平会显著下降,差分运算得出的应变精度也会显著提升。在实际测量过程中,不同程度的数据平滑对最终的应变结果也有显著的影响:数据欠平滑会

导致应变波动较大,而过平滑则会导致丢失高应变梯度信息。因而如何调整平滑参数以保证最佳的平滑效果和最优的应变结果是该算法中重要的一环。研究人员通常根据物体的变形形式来选取不同程度(如线性、二阶等)的数据平滑方法。比如,Germaneau等人^[50,51]采用周围6个相邻点的局部线性平滑方法处理拉伸情况下的位移场;Forsberg等人^[32,33]则采用高阶的切比雪夫多项式近似描述三点弯实验状态下的位移场。

(ii) 局部多项式拟合法。在进行三维应变测量的过程中,DVC方法最为常用的是局部多项式拟合法。该方法通常采用特定阶数(如一阶、二阶等)的多项式拟合计算点周围一定范围内的局部位移数据,随后提取拟合系数中一阶多项式系数来确定各应变分量。由文献调研能够发现,局部多项式拟合通常采用局部最小二乘算法或逐点最小二乘算法。由于变形情况的复杂性,局部拟合过程中所选取的多项式的形式和局部拟合窗口的尺寸也不尽相同。比如Bay等人^[3]采用局部二次多项式拟合已确定的位移场,并将拟合窗口尺寸选取在40~100之间;ZaueI等人^[70]同样采用二阶多项式拟合位移场,并选取了包含60个数据点的应变窗口;Franck等人^[7]采用应变窗口为3³的局部线性最小二乘拟合算法。应当注意的是,对于计算区域边界或者不连续区域附近的计算点,其所在的应变计算窗口也应当包含足够多的数据点,从而保证待定系数的准确计算。此外,人为选取的应变计算窗口的尺寸会直接影响最终的应变计算结果。对于均匀变形,往往推荐使用较大的应变窗口以最大程度压制噪声^[3];而对于非均匀变形,往往需要选取尺寸合适的应变窗口,以期在减小噪声影响和保留变形细节(如高应变区域、应变集中区域等)之间获得最佳的权衡。

(iii) 有限元框架微分法。除此之外,基于有限单元的应变计算方法也被用于DVC中的应变估计,该方法通过直接对节点的位移形函数执行微分运算,从而直接获得全场的三维应变。由于考虑了单元间的位移连续性和协调性,基于有限元思想的应变计算方法通常被认为更加可靠。在实际应变测量过程中,研究人员通常根据试样的变形情况选取不同的体单元以及形函数类型^[87~92]。2010年以来,Limodin和Réthoré等人^[88~91]多次采用C8-DVC方法以及X-C8-DVC方法系统地分析了裂纹萌生或扩展状态下的位

移场和应变场,定量显示了裂纹尖端的应变集中状态. Taillandier-Thomas等人^[92]采用T4有限元框架计算位移场和应变场,验证了在少量投影数据时P-DVC (projection-based DVC)方法能够获得与传统T4-DVC方法相近的应变精度.

2 当前DVC方法所面临的挑战

理论上而言,作为DVC方法的简单二维形式,2D-DIC方法中的多种改进都能够直接拓展并应用到DVC方法中去.然而,由于研究对象、成像方式和图像特性的不同,DVC方法面临着更多的困难和挑战,主要体现在材料微结构、成像误差、算法性能3个方面^[93].

2.1 材料微结构

DVC方法中的位移测量算法依赖于所研究对象成像后的体图像(自身内部纹理)的灰度对比度,由于待研究材料的内部组成和结构通常难以改变,因此图像质量难以人为改进.在某些特殊情况下,可在试样制作成型前混入微型颗粒以增强局部特征^[50,51].然而这些措施会在一定程度上改变材料自身的力学性质,从而对DVC方法的测量结果造成不良影响.在同步加速器设施中,使用相衬技术能够提升材料相位间的差异,从而使其在图像中清晰可见.然而,这种技术并不适用于实验室中的多色X光断层摄影,因此使得DVC技术在处理相位差较弱的材料时困难重重^[94].相比那些具有良好对比度的材料(如岩石、泡沫、松质骨等)以及具有大量内含物的材料(如球墨铸铁、铝铜合金等),DVC方法更加难以处理内部天然纹理较弱的材料,这也成为DVC方法当前面临的一个重要挑战.

2.2 成像误差

在利用CT进行体图像扫描和重建过程中,各种因素(包括统计噪声、射束硬化、X光散射、X射线管温度变化、条纹伪影、环形伪影、移动伪影等)都会对体图像质量造成不良影响^[5,95,96].比如,相邻探测器元件的敏感度差异会在图像重建时引入环形伪影,物体或X光源在扫描时的微小移动会使得投影数据不稳定而造成移动伪影.尤其当块状材料内部的微结构较弱时,这些不良因素在体图像中引入的人工痕迹将会严重影响DVC的计算精度.因此,如何有

效消除图像噪声、人工痕迹等因素以提高DVC测量精度,也是当前DVC研究的挑战之一.

2.3 算法性能

首先,由于三维成像技术的快速发展,高分辨率的体图像已经能够轻易获取.然而,由于普通计算机的内存限制,绝大多数的DVC方法仅仅能够处理远小于 1000^3 voxels的体图像.包含数十亿体素的三维图像通常需要占用数十GB的计算机内存,这显然超出绝大多数普通计算机的能力范围.其次,DVC方法在变形体图像中需要跟踪的是立方子体块,而感兴趣区域扩展成为三维立方体,因此DVC方法的计算量要高出2D-DIC几个数量级,十万个离散数据点在DVC运算时需要近万亿次单精度浮点运算. Gates等人^[97]提出使用现代计算机中多核处理器的并行计算能力提高DVC方法的计算效率,并通过使用CPU和GPU混合并行计算的方式来提高DVC方法的计算效率,使得DVC算法在包含96个核心处理器的计算机组上的运行速度达到330点/秒(子体块尺寸为 41^3 体素). Wang等人^[98]提出一种由GPU加速的DVC方法,该方法结合了精准、高效的三维IC-GN算法,且在普通多核计算机上的运算速度达到了440点/秒(子体块尺寸为 33^3 体素),然而这样的计算效率与实际需求相比仍有较大差距.因此,如何实现计算参数的自适应优化选择,并在普通计算机上普遍实现超大体图像的三维内部变形测量对DVC算法理论提出了更高的要求.

3 总结和展望

作为目前重要的一种能够测量不透明固体材料内部三维运动场的实验力学测试技术,DVC方法实质上是在三维成像技术的基础上发展起来的一种体图像配准方法.自提出以来,受不同学科领域的研究需求、成像设备和计算机的性能提升等因素驱动,DVC方法的基础理论日趋完善,其应用也从初始的生物力学领域逐渐拓展到更为广泛的学科领域,如实验力学、岩土力学、材料科学、生物医学等.该方法被用于各类带有天然纹理或可添加跟踪颗粒的材料(从单相到多相、从脆性到韧性、从固态到半固态、从无机到有机、从天然到合成)在不同载荷状态下(从弹性到塑性、从静态到动态、从拉压到弯扭)的复杂力学信息(如三维变形场、裂纹形貌、SIF、本构参数、

力链等), 为材料和结构的力学建模、数值模拟与实验互验证等方面提供了有力的实验手段。

尽管当前的DVC方法还存在一些局限、困难和挑战, 随着体成像设备的性能提升和使用普及、DVC

方法基础理论的不断突破、计算机性能和高性能计算设备的快速发展, 可以预期, 在实验力学的工具库里DVC方法将扮演更为重要的角色, 并在更多科研和工程领域中获得更为广阔的应用。

参考文献

- Pan B, Qian K, Xie H, et al. Two-dimensional digital image correlation for in-plane displacement and strain measurement: A review. *Meas Sci Tech*, 2009, 20: 062001
- Sutton M A, Orteu J J, Schreier H. *Image Correlation for Shape, Motion and Deformation Measurements: Basic Concepts, Theory and Applications*. New York: Springer, 2009
- Bay B K, Smith T S, Fyhrie D P, et al. Digital volume correlation: Three-dimensional strain mapping using X-ray tomography. *Exp Mech*, 1999, 39: 217–226
- Buffiere J Y, Maire E, Adrien J, et al. *In situ* experiments with X ray tomography: An attractive tool for experimental mechanics. *Exp Mech*, 2010, 50: 289–305
- Limodin N, Réthoré J, Adrien J, et al. Analysis and artifact correction for volume correlation measurements using tomographic images from a laboratory X-ray source. *Exp Mech*, 2011, 51: 959–970
- Benoit A, Guérard S, Gillet B, et al. 3D analysis from micro-MRI during *in situ* compression on cancellous bone. *J Biomech*, 2009, 42: 2381–2386
- Franck C, Hong S, Maskarinec S A, et al. Three-dimensional full-field measurements of large deformations in soft materials using confocal microscopy and digital volume correlation. *Exp Mech*, 2007, 47: 427–438
- Fu J, Pierron F, Ruiz P D. Elastic stiffness characterization using three-dimensional full-field deformation obtained with optical coherence tomography and digital volume correlation. *J Biomed Opt*, 2013, 18: 121512
- Hardisty M R, Whyne C M. Whole bone strain quantification by image registration: A validation study. *J Biomech Eng*, 2009, 131: 064502
- Hussein A I, Barbone P E, Morgan E F. Digital volume correlation for study of the mechanics of whole bones. *Procedia IUTAM*, 2012, 4: 116–125
- Jiroušek O, Jandajsek I, Vavřík D. Evaluation of strain field in microstructures using micro-CT and digital volume correlation. *J Instrum*, 2011, 6: C01039
- Basler S E, Müller T L, Christen D, et al. Towards validation of computational analyses of peri-implant displacements by means of experimentally obtained displacement maps. *Comput Method Biomech*, 2011, 14: 165–174
- Christen D, Levchuk A, Schori S, et al. Deformable image registration and 3D strain mapping for the quantitative assessment of cortical bone microdamage. *J Mech Behav Biomed*, 2012, 8: 184–193
- Pizzo A M, Kokini K, Vaughn L C, et al. Extracellular matrix (ECM) microstructural composition regulates local cell-ECM biomechanics and fundamental fibroblast behavior: A multidimensional perspective. *J Appl Physiol*, 2005, 98: 1909–1921
- Maskarinec S A, Franck C, Tirrell D A, et al. Quantifying cellular traction forces in three dimensions. *Proc Natl Acad Sci USA*, 2009, 106: 22108–22113
- Franck C, Maskarinec S A, Tirrell D A, et al. Three-dimensional traction force microscopy: A new tool for quantifying cell-matrix interactions. *PLoS One*, 2011, 6: e17833
- Notbohm J, Lesman A, Tirrell D A, et al. Quantifying cell-induced matrix deformation in three dimensions based on imaging matrix fibers. *Integr Biol*, 2015, 7: 1186–1195
- Han Y, Kim D W, Kwon H J. Application of digital image cross-correlation and smoothing function to the diagnosis of breast cancer. *J Mech Behav Biomed*, 2012, 14: 7–18
- Girard M J, Strouthidis N G, Desjardins A, et al. *In vivo* optic nerve head biomechanics: Performance testing of a three-dimensional tracking algorithm. *J R Soc Interface*, 2013, 10: 20130459
- Fu J, Haghighi-Abayneh M, Pierron F, et al. Assessment of corneal deformation using optical coherence tomography and digital volume correlation. In: *Mechanics of Biological Systems and Materials*. New York: Springer, 2013. 155–160
- Benoit A, Latour G, Marie-Claire S K, et al. Simultaneous microstructural and mechanical characterization of human corneas at increasing pressure. *J Mech Behav Biomed*, 2016, 60: 93–105

- 22 Sukjamsri C, Gerald D M, Gregory T, et al. Digital volume correlation and micro-CT: An *in-vitro* technique for measuring full-field interface micromotion around polyethylene implants. *J Biomech*, 2015, 48: 3447–3454
- 23 Du J, Lee J H, Jang A T, et al. Biomechanics and strain mapping in bone as related to immediately-loaded dental implants. *J Biomech*, 2015, 48: 3486–3494
- 24 Mostafavi M, McDonald S A, Mummery P M, et al. Observation and quantification of three-dimensional crack propagation in poly-granular graphite. *Eng Fract Mech*, 2013, 110: 410–420
- 25 Mostafavi M, Baimpas N, Tarleton E, et al. Three-dimensional crack observation, quantification and simulation in a quasi-brittle material. *Acta Mater*, 2013, 61: 6276–6289
- 26 Marrow J, Reinhard C, Vertyagina Y, et al. 3D studies of damage by combined X-ray tomography and digital volume correlation. *Procedia Mater Sci*, 2014, 3: 1554–1559
- 27 Morgeneyer T F, Helfen L, Mubarak H, et al. 3D digital volume correlation of synchrotron radiation laminography images of ductile crack initiation: An initial feasibility study. *Exp Mech*, 2013, 53: 543–556
- 28 Buljac A, Taillandier-Thomas T, Morgeneyer T F, et al. Slant strained band development during flat to slant crack transition in AA 2198 T8 sheet: *In situ* 3D measurements. *Int J Fracture*, 2015, 200: 49–62
- 29 Borstnar G, Gillard F, Mavrogordato M N, et al. Three-dimensional deformation mapping of mode I interlaminar crack extension in particle-toughened interlayers. *Acta Mater*, 2016, 103: 63–70
- 30 Rahmani B, Ghossein E, Villemure I, et al. *In-situ* mechanical properties identification of 3D particulate composites using the virtual fields method. *Int J Solids Struct*, 2014, 51: 3076–3086
- 31 Gillard F, Boardman R, Mavrogordato M, et al. The application of digital volume correlation (DVC) to study the microstructural behaviour of trabecular bone during compression. *J Mech Behav Biomed*, 2014, 29: 480–499
- 32 Forsberg F, Mooser R, Arnold M, et al. 3D micro-scale deformations of wood in bending: Synchrotron radiation μ CT data analyzed with digital volume correlation. *J Struct Biol*, 2008, 164: 255–262
- 33 Forsberg F, Sjö Dahl M, Mooser R, et al. Full three-dimensional strain measurements on wood exposed to three-point bending: Analysis by use of digital volume correlation applied to synchrotron radiation micro-computed tomography image data. *Strain*, 2010, 46: 47–60
- 34 Hall S A, Bornert M, Desrues J, et al. Discrete and continuum analysis of localised deformation in sand using X-ray μ CT and volumetric digital image correlation. *Geotechnique*, 2010, 60: 315–322
- 35 Hu Z, Du Y, Luo H, et al. Internal deformation measurement and force chain characterization of mason sand under confined compression using incremental digital volume correlation. *Exp Mech*, 2014, 54: 1575–1586
- 36 Schlüter S, Leuther F, Vogler S, et al. X-ray microtomography analysis of soil structure deformation caused by centrifugation. *Solid Earth*, 2016, 7: 129
- 37 Lenoir N, Bornert M, Desrues J, et al. Volumetric digital image correlation applied to X-ray microtomography images from triaxial compression tests on argillaceous rock. *Strain*, 2007, 43: 193–205
- 38 Mao L, Chiang F P. 3D strain mapping in rocks using digital volumetric speckle photography technique. *Acta Mech*, 2016, 227: 3069–3085
- 39 Mao L, Zuo J, Yuan Z, et al. Full-field mapping of internal strain distribution in red sandstone specimen under compression using digital volumetric speckle photography and X-ray computed tomography. *J Rock Mech Geotech Eng*, 2015, 7: 136–146
- 40 Brault R, Germaneau A, Dupré J C, et al. *In-situ* analysis of laminated composite materials by X-ray micro-computed tomography and digital volume correlation. *Exp Mech*, 2013, 53: 1143–1151
- 41 Tran H, Doumalin P, Delisee C, et al. 3D mechanical analysis of low-density wood-based fiberboards by X-ray microcomputed tomography and digital volume correlation. *J Mater Sci*, 2013, 48: 3198–3212
- 42 Mao L, Chiang F P. Interior strain analysis of a woven composite beam using X-ray computed tomography and digital volumetric speckle photography. *Compos Struct*, 2015, 134: 782–788
- 43 Lecomte-Grosbras P, Réthoré J, Limodin N, et al. Three-dimensional investigation of free-edge effects in laminate composites using X-ray tomography and digital volume correlation. *Exp Mech*, 2015, 55: 301–311
- 44 Saucedo-Mora L, Mostafavi M, Khoshkhou D, et al. Observation and simulation of indentation damage in a SiC-SiC fibre ceramic matrix composite. *Finite Elem Anal Des*, 2016, 110: 11–19
- 45 Hu Z, Luo H, Young W, et al. Incremental digital volume correlation for large deformation measurement of PMI foam in compression. In: *Proceedings of ASME 2012 International Mechanical Engineering Congress and Exposition*. Houston: American Society of Mechanical Engineers, 2012. 721–726
- 46 Berek H, Ballaschk U, Aneziris C G, et al. The correlation of local deformation and stress-assisted local phase transformations in MMC foams. *Mater Charact*, 2015, 107: 139–148

- 47 Patterson B M, Cordes N L, Henderson K, et al. *In situ* X-ray synchrotron tomographic imaging during the compression of hyper-elastic polymeric materials. *J Mater Sci*, 2016, 51: 171–187
- 48 Pierron F, McDonald S A, Hollis D, et al. Comparison of the mechanical behaviour of standard and auxetic foams by X-ray computed tomography and digital volume correlation. *Strain*, 2013, 49: 467–482
- 49 Chu T C, Ranson W F, Sutton M A. Applications of digital-image-correlation techniques to experimental mechanics. *Exp Mech*, 1985, 25: 232–244
- 50 Germaneau A, Doumalin P, Dupré J C. 3D strain field measurement by correlation of volume images using scattered light: Recording of images and choice of marks. *Strain*, 2007, 43: 207–218
- 51 Germaneau A, Doumalin P, Dupré J C. Comparison between X-ray micro-computed tomography and optical scanning tomography for full 3D strain measurement by digital volume correlation. *NDT E Int*, 2008, 41: 407–415
- 52 Tong W. An evaluation of digital image correlation criteria for strain mapping applications. *Strain*, 2005, 41: 167–175
- 53 Pan B, Xie H, Wang Z. Equivalence of digital image correlation criteria for pattern matching. *Appl Opt*, 2010, 49: 5501–5509
- 54 Baldi A, Bertolino F. Experimental analysis of the errors due to polynomial interpolation in digital image correlation. *Strain*, 2015, 51: 248–263
- 55 Luu L, Wang Z, Vo M, et al. Accuracy enhancement of digital image correlation with B-spline interpolation. *Opt Lett*, 2011, 36: 3070–3072
- 56 Bay B K. Methods and applications of digital volume correlation. *J Strain Anal Eng*, 2008, 43: 745–760
- 57 Roberts B C, Perilli E, Reynolds K J. Application of the digital volume correlation technique for the measurement of displacement and strain fields in bone: A literature review. *J Biomech*, 2014, 47: 923–934
- 58 Fedele R, Ciani A, Fiori F. X-ray microtomography under loading and 3D-volume digital image correlation. A review. *Fund Inf*, 2014, 135: 171–197
- 59 Smith T S, Bay B K, Rashid M M. Digital volume correlation including rotational degrees of freedom during minimization. *Exp Mech*, 2002, 42: 272–278
- 60 Gates M, Lambros J, Heath M T. Towards high performance digital volume correlation. *Exp Mech*, 2011, 51: 491–507
- 61 Huang J, Pan X, Li S, et al. A digital volume correlation technique for 3-D deformation measurements of soft gels. *Int J Appl Mech*, 2011, 3: 335–354
- 62 Roeder B A, Kokini K, Robinson J P, et al. Local, three-dimensional strain measurements within largely deformed extracellular matrix constructs. *J Biomech Eng*, 2004, 126: 699–708
- 63 Chiang F P, Mao L. Development of interior strain measurement techniques using random speckle patterns. *Meccanica*, 2015, 50: 401–410
- 64 Pan B, Wu D, Wang Z. Internal displacement and strain measurement using digital volume correlation: A least-squares framework. *Meas Sci Tech*, 2012, 23: 045002
- 65 Pan B, Wang B, Wu D, et al. An efficient and accurate 3D displacements tracking strategy for digital volume correlation. *Opt Laser Eng*, 2014, 58: 126–135
- 66 Tozzi G, Cristofolini L, Viceconti M, et al. Three-dimensional local measurements of bone strain and displacement: Comparison of three digital volume correlation approaches. *J Biomech Eng*, 2015, 137: 1–14
- 67 Leclerc H, Périé J N, Hild F, et al. Digital volume correlation: What are the limits to the spatial resolution. *Mech Ind*, 2012, 13: 361–371
- 68 Madi K, Tozzi G, Zhang Q H, et al. Computation of full-field displacements in a scaffold implant using digital volume correlation and finite element analysis. *Med Eng Phys*, 2013, 35: 1298–1312
- 69 Verhulp E, Van Rietbergen B, Huiskes R. A three-dimensional digital image correlation technique for strain measurements in micro-structures. *J Biomech*, 2004, 37: 1313–1320
- 70 Zauel R, Yeni Y N, Bay B K, et al. Comparison of the linear finite element prediction of deformation and strain of human cancellous bone to 3D digital volume correlation measurements. *J Biomech Eng*, 2006, 128: 1–6
- 71 Niu Y Q, Hu Q S, Yan D Y, et al. Internal 3D displacement analysis using digital image volume correlation method (in Chinese). *J Exp Mech*, 2011, 26: 247–253 [牛永强, 胡秋实, 闫德莹, 等. 基于数字图像体相关的物体内部三维位移场分析. *实验力学*, 2011, 26: 247–253]
- 72 Pan B, Wu D F, Xie H M, et al. Spatial-gradient-based digital volume correlation technique for internal deformation measurement (in Chinese). *Acta Opt Sin*, 2011, 31: 0612005 [潘兵, 吴大方, 谢惠民, 等. 基于梯度的数字体图像相关方法测量物体内部变形. *光学学报*, 2011, 31: 0612005]
- 73 Jandejsek I, Jiroušek O, Vavřík D. Precise strain measurement in complex materials using digital volumetric correlation and time lapse micro-CT data. *Proced Eng*, 2011, 10: 1730–1735

- 74 Baker S, Patil R, Cheung K M, et al. Lucas-kanade 20 years on: Part 5. Technical Report. Pittsburgh: Carnegie Mellon University, 2004. CMU-RI-TR-04-64
- 75 Pan B, Wu D F, Guo B Q. Digital volume image correlation by using iterative least-squares for internal deformation measurement of an object (in Chinese). *J Exp Mech*, 2011, 26: 665–673 [潘兵, 吴大方, 郭保桥. 数字体图像相关方法中基于迭代最小二乘法的物体内部变形测量. *实验力学*, 2011, 26: 665–673]
- 76 Wang M, Hu X F, Wu X P. Digital image correlation method for the analysis of 3-D internal displacement field in object (in Chinese). *Acta Phys Sin*, 2006, 55: 5135–5139 [汪敏, 胡小方, 伍小平. 物体内部三维位移场分析的三维数字图像相关方法. *物理学报*, 2006, 55: 5135–5139]
- 77 Mao L T, Chiang F P, Yuan Z X. Three-dimensional displacement measurement in solid using digital volumetric speckle photography based on computer tomography (in Chinese). *Acta Opt Sin*, 2015, 35: 0312001 [毛灵涛, Chiang Fu-pen, 袁则循. 基于CT的数字体散斑法测量物体内部三维变形场. *光学学报*, 2015, 35: 0312001]
- 78 Bar-Kochba E, Toyjanova J, Andrews E, et al. A fast iterative digital volume correlation algorithm for large deformations. *Exp Mech*, 2015, 55: 261–274
- 79 Roux S, Hild F, Viot P, et al. Three-dimensional image correlation from X-ray computed tomography of solid foam. *Compos Part A-Appl S*, 2008, 39: 1253–1265
- 80 Réthoré J, Tinnés J P, Roux S, et al. Extended three-dimensional digital image correlation (X3D-DIC). *Comptes Rendus Mécanique*, 2008, 336: 643–649
- 81 Leclerc H, Périé J N, Roux S, et al. Voxel-scale digital volume correlation. *Exp Mech*, 2011, 51: 479–490
- 82 Fedele R, Ciani A, Galantucci L, et al. A regularized, pyramidal multi-grid approach to global 3D-volume digital image correlation based on X-ray micro-tomography. *Fund Inf*, 2013, 125: 361–376
- 83 Gomes P L A, Passieux J C, Périé J N. A multigrid PGD-based algorithm for volumetric displacement fields measurements. *Strain*, 2014, 50: 355–367
- 84 Mortazavi F, Ghossein E, Lévesque M, et al. High resolution measurement of internal full-field displacements and strains using global spectral digital volume correlation. *Opt Laser Eng*, 2014, 55: 44–52
- 85 Pan B, Wang B, Lubineau G, et al. Comparison of subset-based local and finite element-based global digital image correlation. *Exp Mech*, 2015, 55: 887–901
- 86 Pan B, Wang B, Lubineau G. Comparison of subset-based local and FE-based global digital image correlation: Theoretical error analysis and validation. *Opt Laser Eng*, 2016, 82: 148–158
- 87 Leclerc H, Roux S, Hild F. Projection savings in CT-based digital volume correlation. *Exp Mech*, 2015, 55: 275–287
- 88 Limodin N, Réthoré J, Buffière J Y, et al. Influence of closure on the 3D propagation of fatigue cracks in a nodular cast iron investigated by X-ray tomography and 3D volume correlation. *Acta Mater*, 2010, 58: 2957–2967
- 89 Rannou J, Limodin N, Réthoré J, et al. Three dimensional experimental and numerical multiscale analysis of a fatigue crack. *Comput Method Appl M*, 2010, 199: 1307–1325
- 90 Limodin N, Réthoré J, Buffière J Y, et al. 3D X-ray microtomography volume correlation to study fatigue crack growth. *Adv Eng Mater*, 2011, 13: 186–193
- 91 Réthoré J, Limodin N, Buffière J Y, et al. Three-dimensional analysis of fatigue crack propagation using X-ray tomography, digital volume correlation and extended finite element simulations. *Proced IUTAM*, 2012, 4: 151–158
- 92 Taillandier-Thomas T, Bouterf A, Leclerc H, et al. Equilibrium gap regularized radio-based digital volume correlation. In: 2nd International Congress on 3D Materials Science. New York: John Wiley & Sons, 2014. 1–8
- 93 Roux S, Taillandier-Thomas T, Bouterf A, et al. Digital volume correlation from tomographic images: Results and challenges. In: Proceedings of IUTAM Symposium on Advances of Optical Methods in Experimental Mechanics. Taipei: Elsevier, 2012
- 94 Liu L, Morgan E F. Accuracy and precision of digital volume correlation in quantifying displacements and strains in trabecular bone. *J Biomech*, 2007, 40: 3516–3520
- 95 Davis G R, Elliott J C. Artefacts in X-ray microtomography of materials. *Mater Sci Tech-Lond*, 2006, 22: 1011–1018
- 96 Boas F E, Fleischmann D. CT artifacts: Causes and reduction techniques. *Imaging Med*, 2012, 4: 229–240
- 97 Gates M, Heath M T, Lambros J. High-performance hybrid CPU and GPU parallel algorithm for digital volume correlation. *Int J High Perform C*, 2014, 29: 92–106
- 98 Wang T, Jiang Z, Kemao Q, et al. GPU accelerated digital volume correlation. *Exp Mech*, 2016, 56: 297–309

Summary for “数字体图像相关方法研究进展”

Research progress in digital volume correlation method

PAN Bing* & WANG Bo

Institute of Solid Mechanics, Beihang University, Beijing 100191, China

* Corresponding author, E-mail: panb@buaa.edu.cn

Full-field displacement and strain measurements of materials, structures and biological tissues subjected to various external (i.e. mechanical or thermal) loading is a primary task of experimental solid mechanics. For nearly a century, benefiting from the rapid development of different branches of physics, various new techniques for whole-field displacement and strain measurements have been developed, advocated and widely used. However, most of these techniques only allows for surface deformation measurement, while in most cases the surface deformation is very different from the actual deformation throughout the interior of a test object. To quantify full-field internal 3D deformation of various opaque materials or biologic tissues subjected to external loading, digital volume correlation (DVC) was developed at the end of last century. Thanks to the increasing popularity and constant emergence of various volumetric imaging devices (e.g., X-ray computed tomography), internal microstructure of a tested sample arising from natural texture or embedded particles can be recorded as digital volume image with distinct random grayscale distribution. By comparing the volume images recorded at different configurations, the internal kinematic field of the sample can be accurately retrieved by DVC algorithm with the assistance of advanced 3D image registration algorithms and modern computational facilities. Benefiting from constant emergence of new 3D imaging facilities, continual refinement of image registration algorithms, and rapid development of high-performance parallel computing technologies, DVC has gained numerous successful applications in biomedicine, solid mechanics, rock and geo mechanics, material science and biomedicines etc. Basically, as an image-based experimental technique, the implementation of DVC for internal deformation measurement comprises two consecutive steps: volume image acquisition using a certain 3D imaging device and image processing using 3D image registration algorithm. Thus, the accuracy and precision of DVC measurements depend on two primary components: the quality of the recorded volumetric images and the performance of DVC algorithms. In order to satisfy the increasing requirement of measurement accuracy in practical applications, many researchers have contributed to investigate the algorithm improvement and imaging error calibration. In the past decade, plenty of methodologies and algorithmic details have been developed to realize higher measurement accuracy and computational efficiency. Although both the image quality and algorithm performance have gain significant improvement in recent years, systematic and random errors inevitably occur during DVC analyses due to the influence of internal microstructure, image acquirement system, loading environment and algorithm details, thus posing important challenge to accurate DVC measurement in practical applications. In this review, the basic principles and procedures of DVC approach and the concept of the algorithmic details are briefly described first. Then, various methodologies and algorithmic details employed in DVC for internal 3D displacement and strain measurement are systematically described and commented. Limitations and potential developments of the technique are also summarized in terms of material microstructure, volumetric imaging and algorithm performance. Despite facing several challenges such as highly dependence on internal microstructure and large data processing with relatively lower computational efficiency, it is foreseen that DVC method will play an increasingly important role in the field of experimental mechanics and definitely expect more potential applications in broad areas especially in material science and biological engineering.

digital volume correlation, internal deformation measurement, experimental mechanics

doi: 10.1360/N972016-00606